

# **AZ** Wastewater Industries, Inc.

Phone: 800 778-9359 Fax: 480 425-3321

www.usa-awi.com

ARIZONA LOCATION: 3201 W. Virginia Ave, Suite 3 Phoenix, AZ 85009 NEVADA LOCATION: 61 Spectrum Blvd Las Vegas, NV 89101

# QUOTE

Quote No.	26337
Quote Date	11/14/2025
Sales Rep.	BLM
Payment Terms	Net 30
F.O.B.	Factory
Prices Good For	60 Days

#### **Customer:**

Lake Havasu City 1150 McCulloch Blvd. North Lake Havasu City, AZ 86403 Attn: Accounts Payable

Item	Item Description	Qty	Unit Cost	Total
900-ECO	Truck Mounted Combination Sewer Cleaner (per the attached specifications)	1	446,169.00	446,169.00T
Discount-Sales	Sourcewell Discount 3% (Contract#101221-SCA)		-3.00%	-13,385.07
Chassis	Chassis Model: Freightliner 114SD Tandem Axle DD13/450 HP	1	154,978.00	154,978.00T
Freight Charge	Freight Charges to Apply	1	8,000.00	8,000.00

Subtotal	\$595,761.93
Sales Tax (8.6%)	\$50,547.52
Total	\$646,309.45

3.5% credit card processing fee will be applied to all invoices paid with credit card







# **Quote# 26337 For Lake Havasu City**

## 900 ECO 12 Yard Combination Sewer Cleaner

#### Vacuum System:

4400 CFM Blower

8" Vacuum Hose system

18" Hg vacuum rating

**Dual Cyclone Separator** 

Dual Element 10 Micron Final Filter

Remote Vacuum Relief Analog Vacuum Display

(6) Tube / Tube Rack

#### Boom:

Telescoping Boom System

Telescoping Reach 17' 2" to 27' 2"

Hydraulic Powered Boom

180° Working Radius Boom Joystick Control

#### **Debris Tank:**

12 Cubic Yard Capacity

Exten Steel Construction

Debris Level Indicator
Hydraulic Dump, 50° Dump Angle (LIFT

CLYINDER)

Dual Ported Rear Door w/ Knife Valve

Dump Height 60"

HOSE REEL ASSEMBLY:

**TOOLBOX CONFIGURATIONS:** 

chas 5RS 16Hd 48QLONES PRESCASUS DENSION FROM TOWALL) DED

Hydraulic Open/Close/Lock Door

#### Water System:

1300 Gallon Capacity Water Tank

Giant plunger style triplex

65 gpm @ 2000 psi w/ 30 min run dry

Black Duraprolene™ Water Tank Construction

w/ 10 Year Warranty

Cold Weather Recirculation System

2.5" Hydrant Fill system

Air Purge Valve

Variable Volume Delivery

Low Water Warning Light

Analog Pressure Display

Front and Mid Ship Hand Gun Ports

#### **Electrical:**

NEMA 4 Control Panel

Hour Meter (Blower & Water Pump)

Military Spec. Sealed Switches

#### Truck

REAR TOOLBOX GROUP W/LONG HANDLE STORAGE (Includes qty 2 4" long handle tool storage tubes, qty 2 24"x18"x18" boxes, and qty 1 63.75"x17.25"12" center section w/pass-through opening. Only available on tandem axle

Mounting to Approved Chassis

(1) Alum Toolbox 24"x42"x100" - Behind Cab

LED D.O.T. Approved Lighting

(2) Tow Hooks Front Bumper

#### Hose Reel & Hose:

Front Mounted Telescoping & Rotating

800' X 1" Hose Capacity

10' Leader Hose

Single Side Controls

#### **Accessories:**

(3) 8" x 6' Extension Tube

(1) 8" X 3' Extension Tube

(1) 8" x 6' Crowned Suction Nozzle

(1) 6" x 10' Flat Discharge Hose

(6) Quick Clamps

BB Hose Guide

Tri-Star (chisel point) nozzle

DD (high flow) nozzle

Finned Nozzle extension

Nozzle Rack (Mounted midship toolbox)

QTY

1

2025

25' Fill Hose

Upstream Pulley Guide

Washdown Gun w/50' of Hose

Cleaner, Tip, Torch, Small

(1) Hydrant Wrench

(1) Paper Owner's Manual

#### **BASE UNIT AS OUTLINED ABOVE**

#### STANDARD OPTIONS:

AUTOMATIC LEVELWIND W/ HYDRAULIC UP/DOWN ACTION	1
DIGITAL 'SMART COUNTER' FOOTAGE METER ±3% ACCURACY	1
FOOTAGE METER (mounted on jetter hose reel)	1
1" ID x 2,500 PSI OPERATING PRESSURE - PER FT	600
WATER PUMPS:	
UPGRADE WATER PUMP TO GIANT 80GPM @ 2,500PSI PLUNGER STYLE TRIPLEX WATER PUMP W/ 30 MINUTE RUN DRY CAPABILITY	1
WATER TANKS:	
ADDITIONAL FULLY BAFFLED 200 GALLON DURAPROLENE™ (BLACK) WATER TANK W/ 10 YEAR WARRANTY (mounted between frame rails - subject to chassis load capacity)	1
DIGITAL WATER TANK LEVEL GAUGE	1
WATER TANK LOW LEVEL AUDIBLE ALARM (level set point is fixed at 150 gallons)	1
DUAL SIDE FILL	1
2" WYE-STRAINER ON INLET FILL SYSTEM	1
WATER SYSTEM ATTACHMENTS:	
FILL HOSE STORAGE RACK	1
CENTRAL WASHDOWN SYSTEM W/ 50FT RETRACTABLE HOSE REEL (mounted at midship)	1

ADD QTY 2 30"X18"X18" PASSENGER SIDE ALUMINUM TOOLBOXES W/ RETRACTABLE 2 STEP LADDER (not	1
available with cold weather hydroexcavation cleaning kit option)  EXPANDED METAL STORAGE BASKET (mounted on driver's side frame rail, not available with driver's side water tank	
or winterization options)	1
DEBRIS BOX & BOOM:	
UPGRADE TO 827 BLOWER (5000CFM @ 18"HG) (Subject to chassis horsepower requirements)	1
DEBRIS LIQUID LEVEL AUDIBLE ALARM (Level set point is adjustable. Tied to vacuum relief and opens vacuum relief	1
valve.)	'
MANUAL/ELECTRIC BOOM CONTORL VALVE (Control valves have built in manual boom control levers. Located at midship.)	1
DEBRIS BODY WASH OUT SYSTEM (includes dual nozzles in debris box)	1
DECANT SCREEN ON REAR DOOR PORT (swing out perforated shield)	<u>.</u> 1
ELECTRICAL & LIGHTING:	
WIRELESS REMOTE PENDANT CONTROL (w/ hose reel payout/retreive, water pump on/off, vacuum relief open/close,	,
boom up/down, boom left/right, boom extend/retract, and kill switch)	1
WIRELESS REMOTE ALARM (buzzer alarm sounds when truck is taken out of neutral with remote not in charging dock)	1
PREMIUM STROBE LIGHT PACKAGE (12 lights total)	1
LED ARROW STICK	1
LED MANHOLE AREA WORK LIGHT	1
LED CURBSIDE BODY MOUNTED WORK LIGHT	1
LED BOOM MOUNTED WORK LIGHTS (2 lights mounted on boom with limb guard)	1
LED REAR MOUNTED WORK LIGHTS (2 lights mounted above rear door)	1
HAND-HELD WIRELESS LED SPOTLIGHT (rechargable with 12v and 110v and includes storage bracket)	1
CHASSIS:  ENHANCED VISIBILITY CAMERA SYSTEM (includes front and rear mounted cameras with split screen monitor in cab)	1
SIX 28" D.O.T. SAFETY CONES AND HOLDER	1
CENTRAL LUBRICATION SYSTEM	1
OLIVITIAL LODIIIOATION OTOTLINI	
PAINT:	
DEBRIS TANK - STANDARD WHITE (specify color in special options)	
BOOM - STANDARD WHITE (specify color in special options)	1
HOSE REEL & UPRIGHT - STANDARD SEWER BLUE (specify color in special options)	'
FRAME & HOSE REEL SLIDE - STANDARD BLACK (specify color in special options)  CONTACT FACTORY FOR METALLIC PAINT AND CLEAR COAT OPTIONS	CONTACT FACTORY
CONTACT FACTORT FOR MILITALLIC FAINT AND GLEAR GOAT OF HONG	CONTACT FACTOR
MANUALS & TRAINING:	
USB OPERATOR'S MANUAL	1
TRAINING AT CUSTOMER'S LOCATION (1 day)	1
	<u> </u>
SPECIAL ITEMS:	
Chassis-Mack Orange P9052	1
Boom Paint - Mack Orange P9052	1
Debris Tank Paint- Mack Orange P9052	1
Hose Reel and Upright Paint- Mack Orange P9052	1
SIGNATURE	DATE


Prepared by:
Andy Ruden
TRUCK COUNTRY OF IOWA,
INC.
3201 HWY 61/151
DUBUQUE, IA 520039695
Phone: 563-556-3773

# A proposal for **SEWER EQUIPMENT CO OF AMERICA BB**

# Prepared by TRUCK COUNTRY OF IOWA, INC. Andy Ruden

Oct 03, 2023

# Freightliner 114SD Plus



Components shown may not reflect all spec'd options and are not to scale



Prepared by:
Andy Ruden
TRUCK COUNTRY OF IOWA,
INC.
3201 HWY 61/151
DUBUQUE, IA 520039695
Phone: 563-556-3773

# SPECIFICATION PROPOSAL

	Data Code	Description	Weight Front	Weight Rear	
Price L	evel				
	PRL-28D	SD PRL-28D (EFF:MY25 ORDERS)			
Data Ve	ersion				
	DRL-014	SPECPRO21 DATA RELEASE VER 014			
Vehicle	Configuration	on			
	001-177	114SD PLUS CONVENTIONAL CHASSIS	7,934	6,476	
	004-225	2025 MODEL YEAR SPECIFIED			
	002-003	SET FORWARD AXLE - TRUCK			
	019-004	STRAIGHT TRUCK PROVISION, NON-TOWING			
	003-001	LH PRIMARY STEERING LOCATION			
Genera	I Service				
	AA1-002	TRUCK CONFIGURATION			
	AA6-002	DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES)			
	99D-010	NO 2008 CARB EMISSION CERTIFICATION			
	AF2-998	NO STATE/PROVINCE INITIAL REGISTRATION SELECTED			
	A85-010	UTILITY/REPAIR/MAINTENANCE SERVICE			
	A84-1GM	GOVERNMENT BUSINESS SEGMENT			
	AA4-002	LIQUID BULK COMMODITY			
	AA5-002	TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS			
	AB1-008	MAXIMUM 8% EXPECTED GRADE			
	AB5-001	SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE			
	995-1AF	FREIGHTLINER LEVEL III WARRANTY			
	A66-99D	EXPECTED FRONT AXLE(S) LOAD: 20000.0 lbs			
	A68-99D	EXPECTED REAR DRIVE AXLE(S) LOAD : 46000.0 lbs			
	A63-99D	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 66000.0 lbs			



	Data Code	Description	Weight Front	Weight Rear
Truck S	Service			
	AA3-034	SEWER/INDUSTRIAL VACUUM BODY		
	AF3-2AA	SEWER EQUIPMENT COMPANY		
Engine				
	101-3CY	DETROIT DD13 GEN 5 12.8L 450 HP @ 1625 RPM, 1900 GOV RPM, 1550 LB/FT @ 975 RPM		
Electro	nic Paramete	ers		
N	79A-074	74 MPH ROAD SPEED LIMIT		
	79B-000	CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT		
	79F-013	FLEET MANAGEMENT - DAILY ENGINE USAGE ENABLED		
	79G-006	5 MINUTES IDLE SHUTDOWN WITH CLUTCH AND SERVICE BRAKE OVERRIDE		
	79K-014	PTO MODE ENGINE RPM LIMIT - 1800 RPM		
	79P-032	PTO RPM CONTROL WITH STEERING WHEEL SWITCHES		
	79S-008	PTO MODE CANCEL VEHICLE SPEED - 25 MPH		
	79T-001	PTO MODE RPM INCREMENT - 25 RPM		
	79U-008	PTO GOVERNOR RAMP RATE - 300 RPM PER SECOND		
	79V-001	FUEL DOSING OF AFTERTREATMENT ENABLED IN PTO MODE-CLEANS HYDROCARBONS AT HIGH TEMPERATURES ONLY		
	79W-011	THREE CLUSTER MENU PTO SPEEDS		
	79X-005	PTO SPEED 1 SETTING - 900 RPM		
	79Y-009	PTO SPEED 2 SETTING - 1400 RPM		
	79Z-006	PTO SPEED 3 SETTING - 1700 RPM		
	80G-002	PTO MINIMUM RPM - 700		
	80L-001	ENABLE AUTO ENGINE RPM ELEVATE FOR EXTENDED IDLE		
	80S-014	PTO 1, NO SWITCH, TEM SUPPLIED REQUEST AND INTERLOCKS, WITH PTO CONNECTIONS, STATIONARY INTERLOCKS		
	80T-014	PTO 2, NO SWITCH, TEM SUPPLIED REQUEST AND INTERLOCKS, WITH PTO CONNECTIONS, STATIONARY INTERLOCKS		
	80V-005	ENGINE MOUNT PTO, TEM SUPPLIED REQUEST, STATIONARY		
	87W-024	PTO 2 MODE ENGINE RPM LIMIT - 1750 RPM		
Engine	Equipment			





Data Code	Description	Weight Front	Weight Rear	
99C-021	2010 EPA/CARB/GHG21 CONFIGURATION			
13E-001	STANDARD OIL PAN			
105-001	ENGINE MOUNTED OIL CHECK AND FILL			
014-1B5	SIDE OF HOOD AIR INTAKE WITH DONALDSON HIGH CAPACITY AIR CLEANER WITH SAFETY ELEMENT, FIREWALL MOUNTED			
124-1E1	DR 12V 200 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE			
292-236	(3) DTNA GENUINE, FLOODED STARTING, MIN 3000CCA, 555RC, THREADED STUD BATTERIES			
290-017	BATTERY BOX FRAME MOUNTED			
281-001	STANDARD BATTERY JUMPERS			
282-001	SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB			
291-017	WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN			
289-001	NON-POLISHED BATTERY BOX COVER			
293-058	POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD DRIVER SEAT	2		
295-029	POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER	2		
306-015	PROGRESSIVE LOW VOLTAGE DISCONNECT AT 12.3 VOLTS FOR DESIGNATED CIRCUITS			
107-046	BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE			
152-041	ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM			
128-002	JACOBS COMPRESSION BRAKE			
016-1C2	RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE	30	25	
28F-014	ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER			
239-026	10 FOOT 06 INCH (126 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT			
237-1CR	RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP			
23U-002	13 GALLON DIESEL EXHAUST FLUID TANK			
30N-003	100 PERCENT DIESEL EXHAUST FLUID FILL			



Data Code	Description	Weight Front	Weight Rear	
23Y-001	STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING			
43X-002	LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION			
43Y-001	STANDARD DIESEL EXHAUST FLUID TANK CAP			
242-001	STAINLESS STEEL AFTERTREATMENT DEVICE/MUFFLER/TAILPIPE SHIELD			
273-059	ELECTRONICALLY CONTROLLED VARIABLE SPEED VISCOUS FAN DRIVE			
276-002	AUTOMATIC FAN CONTROL WITH DASH SWITCH AND INDICATOR LIGHT, NON ENGINE MOUNTED			
110-068	DDC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATER-IN-FUEL INDICATOR			
118-001	FULL FLOW OIL FILTER			
266-107	1400 SQUARE INCH VOCATIONAL RADIATOR			
103-036	ANTIFREEZE TO -34F, ETHYLENE GLYCOL PRE- CHARGED SCA HEAVY DUTY COOLANT			
171-007	GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT			
172-001	CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES			
270-023	HDEP FIXED RATIO COOLANT PUMP AND RADIATOR DRAIN VALVE			
360-013	1350 ADAPTER FLANGE FOR FRONT PTO PROVISION	25		
361-013	FLYWHEEL PTO MOUNTED 1 O'CLOCK WITH 1.217 RATIO AND COMPACT 2000 FLANGE YOKE; REQUIRED VISCOUS DAMPER FOR DRIVESHAFT PROVIDED BY ENGINE MANUFACTURER	50	10	
138-005	PHILLIPS-TEMRO 1500 WATT/115 VOLT BLOCK HEATER	4		
140-053	BLACK PLASTIC ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR			
155-075	MITSUBISHI 12V MOD 3.175-DP60 STARTER WITH INTEGRATED MAGNETIC SWITCH			
Transmission				
342-1M3	ALLISON 4500 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION	260	100	
Transmission Equip	oment			



Data Code	Description	Weight Front	Weight Rear
343-339	ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, HS, MH AND TRV		
84B-012	ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES		
84C-023	PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY		
84D-023	SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY		
84E-017	S5 PERFORMANCE LIMITING PRIMARY SHIFT SCHEDULE, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY		
84F-018	S7 ECONOMY LIMITING SECONDARY SHIFT SCHEDULE, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY		
84G-009	1800 RPM PRIMARY MODE SHIFT SPEED		
84H-009	1800 RPM SECONDARY MODE SHIFT SPEED		
84K-002	2ND GEAR ENGINE BRAKE ALTERNATE PRESELECT WITH MODERATE DOWNSHIFT STRATEGY		
84N-200	FUEL SENSE 2.0 DISABLED - PERFORMANCE - TABLE BASED		
84U-000	DRIVER SWITCH INPUT - DEFAULT - NO SWITCHES		
84V-001	DIRECTION CHANGE ENABLED WITH MULTIPLEXED SERVICE BRAKES - ALLISON 5TH GEN TRANSMISSIONS		
353-076	QUICKFIT BODY LIGHTING CONNECTOR AT END OF FRAME, WITH BLUNTCUTS		
34C-011	ELECTRONIC TRANSMISSION WIRING TO CUSTOMER INTERFACE CONNECTOR		
362-824	(2) CUSTOMER INSTALLED CHELSEA 280 SERIES PTO'S		
363-010	PTO MOUNTING, LH SIDE AND TOP RH SIDE OF MAIN TRANSMISSION ALLISON		
341-018	MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN		
345-003	PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED		
97G-004	TRANSMISSION PROGNOSTICS - ENABLED 2013		



Data Code	Description	Weight Front	Weight Rear	
370-011	WATER TO OIL TRANSMISSION COOLER, FRAME MOUNTED			
346-003	TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK			
35T-001	SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)			
Front Axle and Eq	uipment			
400-1AC	MFS-20-133A 20,000# FL1 71.0 INCH KPI/3.74 INCH DROP SINGLE FRONT AXLE	260		
402-030	MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES	10		
403-002	NON-ASBESTOS FRONT BRAKE LINING			
419-001	CAST IRON OUTBOARD FRONT BRAKE DRUMS			
427-001	FRONT BRAKE DUST SHIELDS	5		
409-006	FRONT OIL SEALS			
408-001	VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL			
416-022	STANDARD SPINDLE NUTS FOR ALL AXLES			
405-002	MERITOR AUTOMATIC FRONT SLACK ADJUSTERS			
406-001	STANDARD KING PIN BUSHINGS			
536-055	TRW THP-60 POWER STEERING WITH RCH45 AUXILIARY GEAR	130		
539-003	POWER STEERING PUMP			
534-003	4 QUART POWER STEERING RESERVOIR			
533-001	OIL/AIR POWER STEERING COOLER			
40T-002	CURRENT AVAILABLE SYNTHETIC 75W-90 FRONT AXLE LUBE			
Front Suspension				
620-006	20,000# FLAT LEAF FRONT SUSPENSION	310		
619-004	GRAPHITE BRONZE BUSHINGS WITH SEALS - FRONT SUSPENSION			
410-998	NO FRONT SHOCK ABSORBERS	-30		
Rear Axle and Equ	ipment			
420-236	RT-46-164 46,000# R-SERIES 78 INCH WIDE TRACK TANDEM REAR AXLE		570	
421-430	4.30 REAR AXLE RATIO			
424-001	IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING			



Prepared by:
Andy Ruden
TRUCK COUNTRY OF IOWA,
INC.
3201 HWY 61/151
DUBUQUE, IA 520039695
Phone: 563-556-3773

Data Code	Description	Weight Front	Weight Rear	
386-075	MXL 18T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES	-10	-10	
388-073	MXL 17T MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH HALF ROUND YOKES			
452-006	DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES		30	
878-022	(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD- REAR AXLE VALVE AND (1) REAR-REAR AXLE VALVE			
87A-017	INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH, DISENGAGE INTERAXLE LOCK WITH IGNITION OFF			
87B-025	INDICATOR LIGHT FOR EACH DIFFERENTIAL LOCKOUT SWITCH, ENGAGE AT SPEEDS 5PMPH OR LESS, DISENGAGE W/IGN OFF			
423-020	MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES			
433-002	NON-ASBESTOS REAR BRAKE LINING			
434-003	STANDARD BRAKE CHAMBER LOCATION			
451-001	CAST IRON OUTBOARD REAR BRAKE DRUMS			
425-002	REAR BRAKE DUST SHIELDS		10	
440-006	REAR OIL SEALS			
426-075	HALDEX GOLDSEAL LONGSTROKE 2-DRIVE AXLES SPRING PARKING CHAMBERS			
428-031	HALDEX AUTOMATIC REAR SLACK ADJUSTERS WITH STAINLESS STEEL CLEVIS PINS			
41T-002	CURRENT AVAILABLE SYNTHETIC 75W-90 REAR AXLE LUBE			
42T-001	STANDARD REAR AXLE BREATHER(S)			
Rear Suspension				
622-1CJ	HENDRICKSON RT463 @46,000# REAR SUSPENSION		750	
621-015	HENDRICKSON RT/RTE - 6.00" SADDLE			
431-001	STANDARD AXLE SEATS IN AXLE CLAMP GROUP			
624-009	54 INCH AXLE SPACING		10	
628-005	STEEL BEAMS AND BRONZE CENTER BUSHINGS WITH BAR PIN ADJUSTABLE END CONNECTIONS			
623-005	FORE/AFT CONTROL RODS			
D : /T = :				



**Pusher / Tag Equipment** 

Data Version PRL-28D.014 SEC\_80958\_MY25



	Data Code	Description	Weight Front	Weight Rear	
	429-998	NO PUSHER/TAG BRAKE DUST SHIELDS			
Brak	e System				
	490-121	WABCO 4S/4M ABS WITH TRACTION CONTROL			
	871-001	REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES			
	904-001	FIBER BRAID PARKING BRAKE HOSE			
	412-001	STANDARD BRAKE SYSTEM VALVES			
	46D-002	STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM			
	413-002	STD U.S. FRONT BRAKE VALVE			
	432-003	RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE			
	480-088	WABCO SYSTEM SAVER HP WITH INTEGRAL AIR GOVERNOR AND HEATER			
*	479-004	AIR DRYER MOUNTED OUTBOARD ON LH RAIL			
		AS CLOSE TO FUEL TANK AS POSSIBLE - REFE RENCI	E NK2385		
*	460-040	STEEL AIR BRAKE RESERVOIRS MOUNTED PERPENDICULAR TO OUTSIDE RAIL			
		MOUNT AFT OF AIR DRYER LIKE NK2385			
	477-011	PETCOCK DRAIN VALVES ON ALL AIR TANK(S)			
Trail	er Connection	าร			
	481-998	NO TRAILER AIR HOSE			
	476-998	NO AIR HOSE HANGER			
*	296-010	PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION			
		296-027: CUSTOMER NEEDS PRE-WIRE FOR STOP/TAI	L/TURN WIRED 1	TO EOF	
	310-998	NO TRAILER ELECTRICAL CABLE			
Whe	elbase & Fran	ne			
	545-698	6975MM (275 INCH) WHEELBASE			
*	546-102	7/16X3-9/16X11-1/8 INCH STEEL FRAME (11.11MMX282.6MM/0.437X11.13 INCH) 120KSI	510	320	
	547-001	1/4 INCH (6.35MM) C-CHANNEL INNER FRAME REINFORCEMENT	240	460	
	552-038	1800MM (71 INCH) REAR FRAME OVERHANG			
	55W-007	FRAME OVERHANG RANGE: 71 INCH TO 80 INCH	-30	130	
	549-002	24 INCH INTEGRAL FRONT FRAME EXTENSION	140	-20	
	AC8-99D	CALC'D BACK OF CAB TO REAR SUSP C/L (CA): 191.14 in			



	Data Code	Description	Weight Front	Weight Rear	
	AE8-99D	CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA): 188.14 in			
	AE4-99D	CALC'D FRAME LENGTH - OVERALL: 397.2 in			
	FSS-0LH	CALCULATED FRAME SPACE LH SIDE: 94.41 in			
	FSS-0RH	CALCULATED FRAME SPACE RH SIDE: 136.02 in			
	553-001	SQUARE END OF FRAME			
	587-003	REAR TOW HOOKS		10	
	550-001	FRONT CLOSING CROSSMEMBER			
	559-001	STANDARD WEIGHT ENGINE CROSSMEMBER			
	562-001	STANDARD MIDSHIP #1 CROSSMEMBER(S)			
	572-001	STANDARD REARMOST CROSSMEMBER			
	565-001	STANDARD SUSPENSION CROSSMEMBER			
Chass	is Equipment				
	556-997	OMIT FRONT BUMPER, CUSTOMER INSTALLED SPECIAL BUMPER, DOES NOT COMPLY WITH FMCSR 393.203	-100		
	585-998	NO MUDFLAP BRACKETS			
	590-998	NO REAR MUDFLAPS			
	551-007	GRADE 8 THREADED HEX HEADED FRAME FASTENERS			
	44Z-002	EXTERIOR HARNESSES WRAPPED IN ABRASION TAPE			
*	606-568	DRLG PREP FOR SEWER EQUIP PER DRAWING 80744-04-V, REV -, 10/21/21			
	605-1AB	D15-16004-000 CENTER PUNCH TO MARK CENTERLINE OF REAR SUSPENSION ON FRAME WEB			
	607-021	CLEAR FRAME RAIL FROM BOC TO FT RR SUSP BRKT, LH RAIL INBOARD			
Fifth V	Vheel				
	578-998	NO FIFTH WHEEL			
Fuel T	anks				
	204-157	110 GALLON/416 LITER ALUMINUM FUEL TANK - LH	20	10	
	218-006	25 INCH DIAMETER FUEL TANK(S)			
	215-005	PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS			
	212-007	FUEL TANK(S) FORWARD			
	664-001	PLAIN STEP FINISH			



	Data Code	Description	Weight Front	Weight Rear	
	205-001	FUEL TANK CAP(S)			
	122-1K3	DAVCO 487 FUEL/WATER SEPARATOR WITH ESOC	15		
	216-020	EQUIFLO INBOARD FUEL SYSTEM			
	20E-004	AUXILIARY FUEL SUPPLY AND RETURN PORTS LOCATED ON LH FUEL TANK			
	202-016	HIGH TEMPERATURE REINFORCED NYLON FUEL LINE			
Tires					
	093-0TB	MICHELIN XZY-3 425/65R22.5 20 PLY RADIAL FRONT TIRES	196		
	094-2H0	CONTINENTAL HD3 HYBRID 11R22.5 14 PLY RADIAL REAR TIRES		136	
Hubs					
	418-060	CONMET PRESET PLUS PREMIUM IRON FRONT HUBS			
	450-060	CONMET PRESET PLUS PREMIUM IRON REAR HUBS			
Whee	ls				
	502-1H5	ALCOA LVL ONE 82462X 22.5X12.25 10-HUB PILOT 4.68 INSET 10-HAND ALUMINUM DISC FRONT WHEELS	-8		
	505-766	ALCOA ULA18X 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS		-248	
N	524-001	POLISHED FRONT WHEELS; OUTSIDE ONLY			
	525-001	POLISHED REAR WHEELS; OUTSIDE OF OUTER WHEELS ONLY			
	496-011	FRONT WHEEL MOUNTING NUTS			
	497-011	REAR WHEEL MOUNTING NUTS			
Cab E	xterior				
	829-1A2	114 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB			
	650-008	AIR CAB MOUNTING			
	648-002	NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE			
	667-001	FRONT FENDERS			
	754-002	3-1/2 INCH FENDER EXTENSIONS	15		
	678-001	LH AND RH GRAB HANDLES			
	645-002	BRIGHT FINISH RADIATOR SHELL/HOOD BEZEL			
	646-042	STATIONARY BLACK GRILLE WITH BRIGHT ACCENTS			



Data Code	Description	Weight Front	Weight Rear	
65X-003	CHROME HOOD MOUNTED AIR INTAKE GRILLE			_
644-004	FIBERGLASS HOOD			
690-002	TUNNEL/FIREWALL LINER			
727-1AH	SINGLE 14 INCH ROUND POLISHED AIR HORN ROOF MOUNTED			
726-001	SINGLE ELECTRIC HORN			
728-001	SINGLE HORN SHIELD			
575-001	REAR LICENSE PLATE MOUNT END OF FRAME			
312-067	HALOGEN COMPOSITE HEADLAMPS WITH BRIGHT BEZELS			
302-047	LED AERODYNAMIC MARKER LIGHTS			
311-003	DAYTIME RUNNING LIGHTS WITH ROCKER/TOGGLE MOMENTARY INTERRUPTER SWITCH			
294-017	INTEGRAL STOP/TAIL/BACKUP LIGHTS WITH 7 EXTRA FEET OF WIRE MOUNTED AT END OF FRAME			
300-015	STANDARD FRONT TURN SIGNAL LAMPS			
744-1BC	DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE			
797-001	DOOR MOUNTED MIRRORS			
796-001	102 INCH EQUIPMENT WIDTH			
743-204	LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS			
* 712-008	(2) CUSTOM NAMEPLATES SHIPPED LOOSE,			
	SEWER EQUIPMENT			
729-001	STANDARD SIDE/REAR REFLECTORS			
677-054	RH AFTERTREATMENT SYSTEM CAB ACCESS WITH PLAIN DIAMOND PLATE COVER			
275-063	2-STAGE ELECTRIC HORN AND HAZARD LAMP ALERT CONTROLLED BY PARTICULATE FILTER REGENERATION REQUIRED STATUS			
764-010	COMPOSITE EXTERIOR SUN VISOR	10		
768-043	63X14 INCH TINTED REAR WINDOW			
661-004	TINTED DOOR GLASS LH AND RH WITH TINTED OPERATING WING WINDOWS			
654-011	RH AND LH ELECTRIC POWERED WINDOWS			
663-013	1-PIECE SOLAR GREEN GLASS WINDSHELD			
659-007	8 LITER (2 GAL) WINDSHIELD WASHER RESERVOIR, CAB MOUNTED, WITHOUT FLUID LEVEL INDICATOR			



Data Code	Description	Weight Front	Weight Rear	
Cab Interior				
055-019	RUGGED TRIM PACKAGE			
707-107	GRAY & CARBON VINYL INTERIOR "RUGGED"			
70K-020	CARBON WITH PREMIUM GUNMETAL ACCENT (RUGGED)			
706-013	MOLDED PLASTIC DOOR PANEL			
708-013	MOLDED PLASTIC DOOR PANEL			
772-006	BLACK MATS WITH SINGLE INSULATION			
785-023	ASH CUP AND LIGHTER			
691-001	FORWARD ROOF MOUNTED CONSOLE			
693-019	LH AND RH DOOR STORAGE POCKETS INTEGRATED INTO MOLDED DOOR PANELS			
738-021	DIGITAL ALARM CLOCK IN DRIVER DISPLAY			
742-007	(2) CUP HOLDERS LH AND RH DASH			
680-029	M2/SD DASH			
700-002	HEATER, DEFROSTER AND AIR CONDITIONER			
701-008	STANDARD HVAC DUCTING WITH SNOW SHIELD FOR FRESH AIR INTAKE			
703-005	MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH			
170-015	STANDARD HEATER PLUMBING			
130-041	VALEO HEAVY DUTY A/C REFRIGERANT COMPRESSOR			
702-002	BINARY CONTROL, R-134A			
739-033	STANDARD INSULATION			
285-013	SOLID-STATE CIRCUIT PROTECTION AND FUSES			
280-007	12V NEGATIVE GROUND ELECTRICAL SYSTEM			
324-1B3	STANDARD LED CAB LIGHTING			
787-998	NO SECURITY DEVICE			
657-001	DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME			
78G-002	KEY QUANTITY OF 2			
655-005	LH AND RH ELECTRIC DOOR LOCKS			
756-338	BASIC ISRINGHAUSEN HIGH BACK AIR SUSPENSION DRIVERS SEAT WTIH MECHANICAL LUMBAR AND INTEGRATED CUSHION EXTENSION	30		



	Data Code	Description	Weight Front	Weight Rear
	760-338	BASIC ISRINGHAUSEN HIGH BACK AIR SUSPENSION PASSENGER SEAT WTIH MECHANICAL LUMBAR AND INTEGRATED CUSHION EXTENSION	25	10
	759-005	DUAL DRIVER AND PASSENGER SEAT ARMRESTS	8	
	711-004	LH AND RH INTEGRAL DOOR PANEL ARMRESTS		
	758-022	BLACK MORDURA CLOTH DRIVER SEAT COVER		
	761-023	BLACK MORDURA CLOTH PASSENGER SEAT COVER		
	763-101	BLACK SEAT BELTS		
	532-002	ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN		
	540-070	4-SPOKE 18 INCH (450MM) LEATHER WRAPPED STEERING WHEEL WITH CHROME SWITCH BEZELS		
	765-002	DRIVER AND PASSENGER INTERIOR SUN VISORS		
Instrun	nents & Contr	rols		
	106-002	ELECTRONIC ACCELERATOR CONTROL		
	732-998	NO INSTRUMENT PANEL-DRIVER		
	734-022	FULLY CONFIGURABLE CENTER INSTRUMENT PANELS		
	870-002	BRIGHT ARGENT FINISH GAUGE BEZELS		
	486-001	LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM		
	840-001	DUAL NEEDLE PRIMARY AND SECONDARY AIR PRESSURE GAUGE		
	198-003	DASH MOUNTED AIR RESTRICTION INDICATOR WITH GRADUATIONS		
	721-001	97 DB BACKUP ALARM		3
	149-015	ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES		
	156-007	KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY		
	811-044	PREMIUM INSTRUMENT CLUSTER WITH 5.0 INCH TFT COLOR DISPLAY		
	81B-003	DIGITAL PANEL LAMP DIMMER SWITCH IN DRIVER DISPLAY		
	160-038	HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH		
	844-001	2 INCH ELECTRIC FUEL GAUGE		



Data	a Code	Description	Weight Front	Weight Rear	
845	-011	FUEL FILTER RESTRICTION INDICATOR			
148	-072	ENGINE REMOTE INTERFACE WITH ONE OR MORE SET SPEEDS			
48H	1-003	QUICKFIT POWERTRAIN INTERFACE CONNECTOR UNDER CAB WITH CAPS			
856	-001	ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE			
854	-008	DIGITAL ENGINE OIL TEMPERATURE IN DRIVER DISPLAY			
852	-002	ELECTRIC ENGINE OIL PRESSURE GAUGE			
864	-001	2 INCH TRANSMISSION OIL TEMPERATURE GAUGE			
867	-004	ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER			
830	-017	ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY			
372	-123	PTO CONTROLS FOR ENHANCED VEHICLE ELECTRIC/ELECTRONIC ARCHITECTURE			
736	-998	NO OBSTACLE DETECTION SYSTEM			
72J-	-998	NO DR ASSIST SYSTEM			
49B	-998	NO VEHICLE STABILITY ADVISOR OR CONTROL			
73B	-998	NO LANE DEPARTURE WARNING SYSTEM			
679	-998	NO OVERHEAD INSTRUMENT PANEL			
1U1	-002	TOP OF DASH RAM MOUNT WITHOUT POWER OR GROUND, FOR CUSTOMER FURNISHED DEVICE			
746	-137	AM/FM/WB WORLD TUNER RADIO WITH BLUETOOTH, USB AND AUXILIARY INPUTS, J1939			
747	-001	DASH MOUNTED RADIO			
750-	-002	(2) RADIO SPEAKERS IN CAB			
753	-001	AM/FM ANTENNA MOUNTED ON FORWARD LH ROOF			
749	-998	NO CB RADIO MOUNTING PROVISION			
74D	-006	STANDARD RADIO WIRING WITH STEERING WHEEL CONTROLS			
810	-027	ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER			
817-	-001	STANDARD VEHICLE SPEED SENSOR			
812	-001	ELECTRONIC 3000 RPM TACHOMETER			
813	-1C8	DETROIT CONNECT PLATFORM HARDWARE			



	Data Code	Description	Weight Front	Weight Rear
	8D1-203	3 YEARS DETROIT CONNECT BASE PACKAGE (FEATURES VARY BY MODEL) DETROIT CONNECT PLATFORM		
	6TS-005	TMC RP1226 ACCESSORY CONNECTOR LOCATED BEHIND PASSENGER SIDE REMOVEABLE DASH PANEL		
	162-002	IGNITION SWITCH CONTROLLED ENGINE STOP		
	81Y-006	PRE-TRIP INSPECTION FEATURE FOR EXTERIOR LAMPS AND SERVICE BRAKES		
	264-030	(1) OVERHEAD MOUNTED LANYARD CONTROL FOR DRIVER AIR HORN		
	883-998	NO TRAILER HAND CONTROL BRAKE VALVE		
	836-015	DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY		
	660-008	SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY		
	304-030	ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS		
	882-009	ONE VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR		
	299-020	SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT		
	298-046	INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH 40 AMP (20 AMP PER SIDE) TRAILER LAMP CAPACITY		
	87T-998	NO WRG/SW-OPTL #2,CHAS,AIR		
Design				
	065-000	PAINT: ONE SOLID COLOR		
Color				
	980-5F6	CAB COLOR A: L0006EY WHITE ELITE EY		
	986-020	BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT		
	976-995	SUNVISOR PAINTED SAME AS CAB COLOR A		
	963-003	STANDARD E COAT/UNDERCOATING		
Certifica	ation / Compl	iance		
	996-001	U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS		
Second	ary Factory C	ptions		



Data Code	Description	Weight Front	Weight Rear	
999-051	FRONT AND/OR REAR TIRE WIDTH EXCEEDS 2.6 M (102.4") AND CHASSIS MODIFICATIONS MAY BE REQUIRED DUE TO POSSIBLE PTO/CHASSIS INTERFERENCE;CUSTOMER ADVISED & ACCEPTS			
Sales Programs				
	NO SALES PROGRAMS HAVE BEEN SELECTED			
	TOTAL VEHICLE SU	M M A R	Y	

Weight Summary			
	Weight Front	Weight Rear	Total Weight
Factory Weight <sup>+</sup>	10053 lbs	8782 lbs	18835 lbs
Total Weight <sup>+</sup>	10053 lbs	8782 lbs	18835 lbs



<sup>(+)</sup> Weights shown are estimates only.

If weight is critical, contact Customer Application Engineering.

<sup>(\*\*\*)</sup> All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.

Prepared by:
Andy Ruden
TRUCK COUNTRY OF IOWA,
INC.
3201 HWY 61/151
DUBUQUE, IA 520039695
Phone: 563-556-3773

#### QUOTATION

#### 114SD PLUS CONVENTIONAL CHASSIS

SET FORWARD AXLE - TRUCK
DETROIT DD13 GEN 5 12.8L 450 HP @ 1625 RPM, 1900
GOV RPM, 1550 LB/FT @ 975 RPM

ALLISON 4500 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION

RT-46-164 46,000# R-SERIES 78 INCH WIDE TRACK TANDEM REAR AXLE

HENDRICKSON RT463 @46,000# REAR SUSPENSION MFS-20-133A 20,000# FL1 71.0 INCH KPI/3.74 INCH DROP SINGLE FRONT AXLE

20.000# FLAT LEAF FRONT SUSPENSION

114 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB
6975MM (275 INCH) WHEELBASE
NO FIFTH WHEEL
7/16X3-9/16X11-1/8 INCH STEEL FRAME
(11.11MMX282.6MM/0.437X11.13 INCH) 120KSI
1800MM (71 INCH) REAR FRAME OVERHANG
1/4 INCH (6.35MM) C-CHANNEL INNER FRAME
REINFORCEMENT



Prepared for:
John Wichmann
SEWER EQUIPMENT CO OF
AMERICA BB
1590 DUTCH RD
DIXON II 61021

DIXON, IL 61021 Phone: 815-835-5566 Prepared by:
Andy Ruden
TRUCK COUNTRY OF IOWA,
INC.
3201 HWY 61/151
DUBUQUE, IA 520039695
Phone: 563-556-3773

# **Daimler Truck Financial**


Financing that works for you.

See your local dealer for a competitive quote from Daimler Truck Financial, or contact us at Information@dtfoffers.com.

Daimler Truck Financial offers a variety of finance, lease and insurance solutions to fit your business needs. For more information about our products and services, visit our website at <a href="www.daimler-truckfinancial.com">www.daimler-truckfinancial.com</a>.



Prepared by:
Andy Ruden
TRUCK COUNTRY OF IOWA,
INC.
3201 HWY 61/151
DUBUQUE, IA 520039695
Phone: 563-556-3773



#### **VEHICLE SPECIFICATIONS SUMMARY - DIMENSIONS**

Model	114SD
Wheelbase (545)	6975MM (275 INCH) WHEELBASE
Rear Frame Overhang (552)	1800MM (71 INCH) REAR FRAME OVERHANG
Fifth Wheel (578)	NO FIFTH WHEEL
Mounting Location (577)	NO FIFTH WHEEL LOCATION
Maximum Forward Position (in)	0
	0
Amount of Slide Travel (in)	0
Slide Increment (in)	0
Desired Slide Position (in)	0.0
	114 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB
Sleeper (682)	NO SLEEPER BOX/SLEEPERCAB
Exhaust System (016)RH OUTBOARD UNDER STEP MC	DUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY

#### **TABLE SUMMARY - DIMENSIONS**



Prepared by:
Andy Ruden
TRUCK COUNTRY OF IOWA,
INC.
3201 HWY 61/151
DUBUQUE, IA 520039695
Phone: 563-556-3773


Dimensions	Inches	
Bumper to Back of Cab (BBC)	132.9	
Bumper to Centerline of Front Axle (BA)	49.4	
Front Axle to Back of Cab (AC)	83.5	
Min, Cab to Body Clearance (CB)	3.0	
Back of Cab to Centerline of Rear Axle(s) (CA)	191.1	
Effective Back of Cab to Centerline of Rear Axle(s) (Effective CA)	188.1	
Back of Cab Protrusions (Exhaust/Intake) (CP)	3.8	
Back of Cab Protrusions (Side Extenders/Trim Tab) (CP)	0.0	
Back of Cab Protrusions (CNG Tank)	0.0	
Back of Cab Clearance (CL)	3.0	
Back of Cab to End of Frame	262.0	
Cab Height (CH)	71.8	
Wheelbase (WB)	274.6	
Frame Overhang (OH)	70.9	
Overall Frame Length	397.2	
Overall Length (OAL)	394.9	
Rear Axle Spacing	54.0	
Unladen Frame Height at Centerline of Rear Axle	43.1	

Performance calculations are estimates only. If performance calculations are critical, please contact Customer Application Engineering.



Prepared by:
Andy Ruden
TRUCK COUNTRY OF IOWA,
INC.
3201 HWY 61/151
DUBUQUE, IA 520039695
Phone: 563-556-3773

### TRUCK WEIGHT



#### **VEHICLE SPECIFICATIONS SUMMARY - TRUCK WEIGHT**

Model	114SD
Cab Size (829)	ROOF ALUMINUM CONVENTIONAL CAB
Expected Front Axle(s) Load (lbs)	20000.0
Expected Pusher Axle(s) Load (lbs)	0.0
Expected Rear Axle(s) Load (lbs)	46000.0
Expected Tag Axle(s) Load (lbs)	0.0
Expected GVW (lbs)	66000
Expected GCW (lbs)	0.0
Wheelbase (545)	6975MM (275 INCH) WHEELBASE
Pusher / Tag Axle (443)	NO PUSHER OR TAG AXLE
Front Axle to Back of Cab (in)	83.464
Cab to Body Clearance (in)	3.0
Front Axle to Body (in)	86.464
Truck Configuration (AA3)	SEWER/INDUSTRIAL VACUUM BODY
Body Length (ft)	11.8
Body Weight (lbs)	1700.0
Body Horiz CG from Body Front (ft)	5.5
Body Front to Rear Axle(s) CL (ft)	15.68
Driver Weight (lbs)	500.0
Driver Horizontal CG from Front Axle (in)	
Left-Hand Primary Fuel/Hydraulic Tank (204)110 GALLO	N/416 LITER ALUMINUM FUEL TANK - LH
Left Fuel Tank Horizontal CG (in)	101.153
Right-Hand Primary Fuel/Hydraulic Tank (206)	NO RH FUEL TANK



Prepared by:
Andy Ruden
TRUCK COUNTRY OF IOWA,
INC.
3201 HWY 61/151
DUBUQUE, IA 520039695
Phone: 563-556-3773

Right Fuel Tank Horizontal CG (in) ......0

#### **TABLE SUMMARY - TRUCK WEIGHT**

Item	Front(s)	Rear(s)	Total
	All Control of the Co	1)	
Chassis Tare	10053	8782	18835
Fuel / Oil	591	319	910
Driver	431	69	500
Dealer Installed Options	0	0	0
Accessories Total	0	0	0
Body Tare	756	944	1700
Truck Tare Weight	11831	10114	21945
Payload Total	0	0	0
Calculated Axle Loads	11831	10114	21945
Expected Axle Loads / GVW	20000	46000	66000
GAWR / GVWR	20000	46000	66000
Payload CG From Front of Body		5.9 feet	
Payload CG From Front Axle		13.1 feet	
Payload Distribution		Variable	
All v	veights displayed in pounds		

Item	Front(s)	Rear(s)	Total
Chassis Tare	10053	8782	18835
Fuel / Oil	591	319	910
Driver	431	69	500
Dealer Installed Options	0	0	0
Accessories Total	0	0	0
Body Tare	756	944	1700
Truck Tare Weight	11831	10114	21945
Payload Total	0	0	0
Calculated Axle Loads	11831	10114	21945
Expected Axle Loads / GVW	20000	46000	66000
GAWR / GVWR	20000	46000	66000
Payload CG From Front of Body		5.9 feet	
Payload CG From Front Axle		13.1 feet	
Payload Distribution		Variable	
All v	veights displayed in pounds		



Prepared by:
Andy Ruden
TRUCK COUNTRY OF IOWA,
INC.
3201 HWY 61/151
DUBUQUE, IA 520039695
Phone: 563-556-3773

Performance calculations are estimates only. If performance calculations are critical, please contact Customer Application Engineering.

